

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### LARGE VANDAL RESISTANT

#### APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

#### ELECTRICAL

UL and CSA<sub>US</sub> listed for wet and damp locations.

#### LENS

One piece, injection molded, heat resistant polycarbonate with UV inhibitors to reduce yellowing.

#### HOUSING

Die cast housing with chromate conversion coating and a textured bronze finish.



#### DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
VRL84EL	12 3/8"	12 3/8"	8 5/8"
VRL26MG	12"	12"	5 1/2"
VRL52EL	12"	12"	5 1/2"

#### REFLECTOR

One piece anodized aluminum reflector provides controlled high intensity.

#### ADDITIONAL FEATURES

- Available in fluorescent or wired.

### ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
VRL84EL	2 x 42W	Full Electronic
VRL26MG	2 x 13W	Magnetic
VRL52EL	2 x 26W	Full Electronic

#### ACCESSORIES

Clear Lens - PC
White Lens - PW
Internal Reflector - IR
External Hood - EH