

TEDDICO

LIGHTING SPECIFICATION SHEET

CONSTELLATION "FULL CUTOFF" WALL PACKS

APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

HOUSING

Die Cast front and rear housing with tempered glass lens and built-in template for mounting to an electrical box. There is a chromate conversion coating with a textured bronze finish.



DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
WPFC175	14 1/4"	9 1/8"	11 3/8"
WPFC250	18 1/4"	9 1/8"	13 3/4"
WPFC150	18 1/4"	9 1/8"	7 1/8"

REFLECTOR

2-piece pinged aluminum reflector with porcelain socket and bracket.

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Reusable Styrofoam and inner carton
- Meets local "Dark Sky" requirements
- Also available in white

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
METAL HALIDE		
WPFC100MH	100	Multi-Tap
WPFC150MH	150	Multi-Tap
WPFC175MH	175	Multi-Tap
WPFC175MH	175	Multi-Tap
WPFC250MH	250	Multi-Tap
WPFC400MH	400	Multi-Tap
WPFC320MH	320	Multi-Tap
HIGH PRESSURE SODIUM		
WPFC150	150	120 Volt
WPFC250	250	Multi-Tap
WPFC400	400	Multi-Tap

ACCESSORIES

Flat Glass Lens
Clear Glass
Etched Glass
Prismatic Glass
ColorLIFE Lens
ColorLIFE-YELLOW
ColorLIFE-LIGHT BLUE