

TEDDICO

LIGHTING SPECIFICATION SHEET

GARAGE LIGHTER

APPLICATION:

Ideal low wattage energy saving luminaire that provides economic cost for exterior ceiling mounting for parking garages, perimeter lighting, entrance and walkways, building eaves and canopies, correctional institutions, schools, shopping centers and terminals. Special energy efficient Uni-Form Pulse Start Metal Halide ballast and lamps are also available.

ELECTRICAL

UL listed for damp locations for ceiling mount.

DIFFUSER

One piece, high impact, clear prismatic polycarbonate with ultraviolet inhibitors to minimize discoloration. Gasketed to eliminate moisture, dust and insects.

HOUSING

One piece heavy die duty cast back housing. Features three convenient 1/2" side hubs for surface mounting and one rear 1/2" hub for ceiling mount. Polyester powder coat paint finish, BRONZE.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	Lbs.
HIGH PRESSURE SODIUM			
GLVR150	150	120/Reactor NPF	14
GLVR150MT	150	Multi-tap HPF	19
METAL HALIDE			
GLVR175	175	Multi-tap CWA	18
PULSE START METAL HALIDE			
GLVR100MH	100	Multi-tap CWA	18
GLVR125MH	125	Multi-tap CWA	18
GLVR150MH	150	Multi-tap CWA	18
GLVR175MH	175	Multi-tap CWA	18



DIMENSIONS

Width	Height	Depth
15" RND	11-1/4"	-

REFLECTOR

Highly polished aluminum

BALLAST

Class H insulated, NPF 120v 60 Hz reactor
High pressure sodium and HPF Quad volt
60Hz Metal Halide and HPS.

ADDITIONAL FEATURES

- Three 1/2" tapped side holes for securing conduit
- Porcelain medium base socket

ACCESSORIES

Quartz Restrike suffix - QZ
Pendant Mount Swivel - CPSPS
Downrods