

TEDDICO

LIGHTING SPECIFICATION SHEET

“MAXI LIGHTER” AREA or GARAGE LIGHTER

APPLICATION:

Ideal low wattage energy saving luminaire that provides economic cost for exterior ceiling mounting for parking garages, perimeter lighting, entrance and walkways, building eaves and canopies, correctional institutions, schools, shopping centers and terminals. Special energy efficient Uni-Form Pulse Start Metal Halide ballast and lamps are also available.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

HOUSING

Square die cast back housing and front frame, chromate conversion coating with a textured bronze finish.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
HIGH PRESSURE SODIUM		
MAXGL250	250	Multi-Tap
MAXGL400	400	Multi-Tap
METAL HALIDE		
MAXGL250MH	250	Multi-Tap
MAXGL400MH	400	Multi-Tap



DIMENSIONS

Width	Height	Depth
16"	17"	14"

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Coin plugs on sides and back
- Extended vandal resistant polycarbonate lens with stainless steel screws
- Gasket
- Aluminum Reflector
- Porcelain Mogul Base Socket and Bracket
- Vertical Lamp Mount
- Master Carton

ACCESSORIES

Swivel Bracket
Slip Fitter
External Mount Slip Fitter
Slip Fitter Cover with 1" Plug
Extruded Mounting Arms