

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### HID WORKLIGHT

#### APPLICATION:

Designed as a temporary fixture for construction sites. Can be used anywhere temporary lighting is required. Also available with energy saving pulse start metal halide ballasts and lamps. Also available with special open rated PSMH lamps.

#### ELECTRICAL

UL and CSA<sub>us</sub> listed for wet and damp locations.

#### HOUSING

Heavy duty die cast aluminum with splice box and hook. Gasketed to reduce dirt contamination and extend ballast life and performance. Polyester powder coat finish - WHITE.



#### DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
WK150	9"	27-3/4"	9-1/2"

#### BALLAST

Class H insulated, NPF 120v 60 Hz reactor High Pressure Sodium, Multi-tap ballasts are CWA autotransformers.

#### WIRE GUARD

Zinc plated steel, "open-close" type

#### ADDITIONAL FEATURES

- Adjustable bracket
- Porcelain mogul base socket
- Lamp included

#### ACCESSORIES

Quartz restrike 150 watt suffix - Z

Cordset 120 volt suffix - 120C

Cordset 240 volt suffix - 240C

Cordset 277 volt suffix - 277C

\* Requires shrouded open fixture rated lamp.

### ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	LBS.
<b>METAL HALIDE</b>			
WK400MH*	400	Multi-tap CWA	23
<b>PULSE START METAL HALIDE</b>			
WK200MH*	200	Multi-tap CWA	24
WK250PSMH*	250	Multi-tap CWA	24
WK300MH*	300	Multi-tap CWA	24
WK320MH*	320	Multi-tap CWA	24
WK350MH*	350	Multi-tap CWA	24
WK400PSMH*	400	Multi-tap CWA	24