

TEDDICO

LIGHTING SPECIFICATION SHEET

LARGE WALLPACK

APPLICATION:

Ideal high wattage luminaire for mounting heights above 15 feet for exterior wall and area lighting for parking areas, perimeter lighting, entrance and walkways, loading platforms, and warehouses. Special energy efficient Uni-form Pulse Start Metal Halide ballast and lamps are also available.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

LENS

One piece, high impact, heat resistant, borosilicate glass for wide spread distribution of light.

HOUSING

Two piece heavy duty die cast aluminum. Face frame is hinged and secured to back box with two stainless steel screws. This design allows for easy access for relamping. Polyester powder coat paint finish, BRONZE.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	Lbs.
HIGH PRESSURE SODIUM			
WP250	250	Multi-Tap	31
WP400	400	Multi-Tap	31
METAL HALIDE			
WP250MH	250	Multi-Tap	29
WP400MH	400	Multi-Tap	31
PULSE START METAL HALIDE			
WP200MH	200	Multi-Tap	31
WP250PSMH	250	Multi-Tap	31
WP300MH	300	Multi-Tap	31
WP320MH	320	Multi-Tap	31
WP350MH	350	Multi-Tap	32
WP400PSMH	400	Multi-Tap	32



DIMENSIONS

Width	Height	Depth
18"	9"	12 3/4"

REFLECTOR

One piece stippled asymmetric anodized aluminum designed in conjunction with the diffuser for efficient light distribution.

BALLAST

Class H insulated, CWA Multi-tap 60Hz.

ADDITIONAL FEATURES

- Two 1/2" tapped side holes for securing conduit.
- One 1/2" tapped hole for mounting photo cell
- Porcelain Mogul socket

ACCESSORIES

Wire Guard suffix - WG
Photo Cell - 120 volt suffix - PC
Photo Cell 208-277 volt suffix - PC2
Polycarbonate Guard - PG