

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### MEDIUM FLOODLIGHT

#### APPLICATION:

Lower wattage luminaire that provides economic cost for exterior security lighting applications for commercial building facades, parking areas, perimeter lighting, recreational areas, display, sign lighting and landscape lighting.

#### ELECTRICAL

UL and CSA<sub>us</sub> listed for wet and damp locations.

#### DIFFUSER

One piece high impact tempered glass lens.

#### HOUSING

The one piece heavy duty cast aluminum face frame is hinged and secured to the back box with captive screws. Powder coat Bronze finish. 1/2" NPT threaded mounting swivel.

### ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	Lbs.
<b>HIGH PRESSURE SODIUM</b>			
FL100	100	120 Volt/Reactor	13
FL150	150	120 Volt/Reactor	13
<b>METAL HALIDE</b>			
FL175MH	175	Multi-Tap	15
<b>PULSE START METAL HALIDE</b>			
FL70MH	70	Multi-Tap	15
FL100MH	100	Multi-Tap	15
FL125MH	125	Multi-Tap	15
FL150MH	150	Multi-Tap	15
FL175PSMH	175	Multi-Tap	15



#### DIMENSIONS

Width	Height	Depth
9-3/4"	9-3/4"	6-3/4"

#### REFLECTOR

A one piece anodized aluminum reflector provides wide beam distribution.

#### BALLAST

Class H insulated, CWA Multi tap

#### MOUNTING

Wall or pole mount.

#### ADDITIONAL FEATURES

- Photo cell adaptable
- Porcelain mogul base socket
- Lamp included

#### ACCESSORIES

- Glare Shield suffix - GS
- Photo Cell - 120 suffix- PC
- Photo Cell 208-277 volt suffix- PC2