

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### MEDIUM WALLPACK

#### APPLICATION:

Ideal high wattage luminaire for mounting heights below 15 feet for exterior wall and area lighting for parking areas, perimeter lighting, entrance and walkways, loading platforms, and warehouses. Special energy efficient Uni-form Pulse Start Metal Halide ballast and lamps are also available.

#### ELECTRICAL

UL and CSA<sub>us</sub> listed for wet and damp locations.

#### LENS

One piece, high impact, heat resistant, borosilicate glass for wide spread distribution of light.

#### HOUSING

Die cast housing with a Borosilicate molded glass lens, gasket, chromate conversion coating, and a textured bronze finish.

### ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
<b>HIGH PRESSURE SODIUM</b>		
WP150	150	120 Volt
WP150MT	150	Multi-Tap
<b>METAL HALIDE</b>		
WP50MH	50	Multi-Tap
WP70MH	70	Multi-Tap
WP100MH	100	Multi-Tap
WP175MH	175	Multi-Tap
WP175PSMH	175	Multi-Tap



#### DIMENSIONS

	Width	Height	Depth
WP15	14"	9"	7"

#### REFLECTOR

The medium wall pack has a combination barrier-reflector.

#### BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

#### ADDITIONAL FEATURES

- Medium Base socket and bracket
- Reusable Styrofoam and inner carton

#### ACCESSORIES

Wire Guard
Full Cut Off*
Side Cut Off*
Polycarbonate Guard
* Specify "A" for Aluminum and "S" for Steel