

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### ROUND BACK FLOOD

#### APPLICATION:

Lower wattage luminaire that provides exterior security lighting applications for commercial building facades, parking areas, perimeter lighting, recreational areas, display, sign lighting and landscape lighting.

#### ELECTRICAL

UL and CSA<sub>us</sub> listed for wet and damp locations.

#### DIFFUSER

One piece high impact tempered glass lens.

#### HOUSING

The one piece heavy duty cast aluminum face frame is hinged and secured to the back box with captive screws. Powder coat Bronze finish. 1/2" NPT threaded mounting swivel.



#### DIMENSIONS

Width	Height	Depth
11"	8-1/2"	7-3/4"

#### REFLECTOR

A one piece anodized aluminum reflector provides wide beam distribution.

#### BALLAST

Class H insulated, CWA Multi tap

#### MOUNTING

UL listed for mounting within 4" of the ground.

#### ADDITIONAL FEATURES

- Porcelain mogul base socket
- Lamp included

## ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	Lbs.
<b>HIGH PRESSURE SODIUM</b>			
RFL100	100	Multi-Tap CWA	13
RFL150	150	Multi-Tap CWA	13
<b>METAL HALIDE</b>			
RFL175MH	175	Multi-Tap CWA	15
<b>PULSE START METAL HALIDE</b>			
RFL100MH	100	Multi-Tap CWA	15
RFL125MH	125	Multi-Tap CWA	15
RFL150MH	150	Multi-Tap CWA	15
RFL175PSMH	175	Multi-Tap CWA	15