

TEDDICO

LIGHTING SPECIFICATION SHEET

SCONCE WALL PACKS

APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

HOUSING

Die cast housing with flat tempered prismatic glass lens, chromate conversion coating and textured bronze finish.



DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
WPSC150	14 1/4"	9"	7 1/4"
WPSC250	18 1/8"	9"	12 7/8"

REFLECTOR

Two-piece pinged aluminum reflector with porcelain socket and bracket.

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Porcelain medium base socket and bracket for medium
- Porcelain mogul base socket and bracket for large
- Semi-cutoff design

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
METAL HALIDE		
WPSC100MH	100	Multi-Tap
WPSC150MH	150	Multi-Tap
WPSC175MH	175	Multi-Tap
WPSC175MH	175	Multi-Tap
WPSC250MH	250	Multi-Tap
WPSC400MH	400	Multi-Tap
HIGH PRESSURE SODIUM		
WPSC150	150	120 Volt
WPSC250	250	Multi-Tap
WPSC400	400	Multi-Tap