

TEDDICO

LIGHTING SPECIFICATION SHEET

SLIM LINE WALLPACK

APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

HOUSING

Die Cast housing and hinged front frame with a chromate conversion coating and a textured bronze finish. The Slimline Wall Pack comes with molded Borosilicate prismatic glass lens.



DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
WPSL400	16 1/2"	17 3/8"	7"

REFLECTOR

The reflector has porcelain mogul base socket and bracket with side access to the conduit.

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Includes mounting plate with integral electrical box

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	
METAL HALIDE			
WPSL175MH	175	Multi-Tap	
WPSL250MH	250	Multi-Tap	
WPSL400MH	400	Multi-Tap	
HIGH PRESSURE SODIUM			
WPSL250	250	Multi-Tap	
WPSL400	400	Multi-Tap	
PULSE START METAL HALIDE			
WP200MH	200	Multi-Tap	31
WP250PSMH	250	Multi-Tap	31
WP300MH	300	Multi-Tap	31
WP320MH	320	Multi-Tap	31
WP350MH	350	Multi-Tap	32
WP400PSMH	400	Multi-Tap	32