

TEDDICO

LIGHTING SPECIFICATION SHEET

SMALL WALLPACK

APPLICATION:

Ideal low wattage energy saving luminaire that provides economic cost and vandal resistance for exterior wall and area lighting for parking areas, perimeter lighting, entrance and walkways, loading platforms, and warehouses.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

DIFFUSER

One piece, injection molded, heat resistant clear polycarbonate lens with UV inhibitors. Front hinged and secured with four screws. A borosilicate molded prismatic glass lens with die cast frame is also available.

HOUSING

One piece, heavy duty, die cast aluminum. Polyester powder coat paint finish, BRONZE.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	Lbs.
HIGH PRESSURE SODIUM			
WP35	35	120/Reactor NPF	8
WP50	50	120/Reactor NPF	8
WP70	70	120/Reactor NPF	9
WP100	100	120/Reactor NPF	9
WPG100	100	120/Reactor NPF	12
WPG150	150	120/Reactor NPF	12
METAL HALIDE			
WPG70MH	70	Multi-tap HX-HPF	15
WPG100MH	100	Multi-tap HX-HPF	15



DIMENSIONS

Width	Height	Depth
8 1/2"	8 1/2"	9"

REFLECTOR

One piece, semi specular asymmetric anodized aluminum for optimum efficiency.

BALLAST

Class H insulated, NPF 120v 60 Hz reactor
High pressure sodium. Metal Halide Multi-tap.

ADDITIONAL FEATURES

- Two 1/2" tapped side holes for securing conduit.
- One 1/2" tapped hole for mounting photo cell
- Porcelain medium base socket
- Optional mounting cover and threaded stem
- Lamp included

ACCESSORIES

Wire Guard suffix - WG
Photo Cell - 120 volt suffix - PC
Glass Lens (WPG)