

# TEDDICO

## LIGHTING SPECIFICATION SHEET

### VANDAL RESISTANT FLUORESCENT ENTRY LIGHT

**APPLICATION:**

Ideal low wattage energy saving luminaire that provides economic cost for exterior/interior ceiling or wall mounting for parking garages, perimeter lighting, entrance and walkways, building eaves and canopies, correctional institutions, schools, shopping centers and terminals.

**ELECTRICAL**

UL and CSA<sub>us</sub> listed for wet and damp locations.

**HOUSING**

Die cast housing with a Chromate Conversion Coating, polycarbonate lens with gasket (deep or shallow). Master carton available painted in black and white and all white or as an unfinished casting net.

### ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
VR26WH	2x13	120 Volt
VR26BZ	2x13	120 Volt
VR26BL	2x13	120 Volt



**DIMENSIONS**

	Width	Height	Depth
VR26WH	5 1/8"	13 1/4"	3"

**BALLAST**

Magnetic Fluorescent Ballast.

**ADDITIONAL FEATURES**

- Galvanized back pan
- Inner carton
- Master carton

**ACCESSORIES**

- Clear Polycarbonate Shallow Lens
- Clear Polycarbonate Deep Lens