

TEDDICO

LIGHTING SPECIFICATION SHEET

VANDAL RESISTANT GARAGE LIGHTER

APPLICATION:

Ideal low wattage energy saving luminaire that provides economic cost for exterior ceiling mounting for parking garages, perimeter lighting, entrance and walkways, building eaves and canopies, correctional institutions, schools, shopping centers and terminals. Special energy efficient Uni-Form Pulse Start Metal Halide ballast and lamps are also available.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

DIFFUSER

One piece, injection molded, heat resistant polycarbonate with UV inhibitors to reduce yellowing.

HOUSING

Die cast back housing with built-in template for mounting to an electrical box and chromate conversion coating.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
HIGH PRESSURE SODIUM		
GLVR150	150	120 Volt
METAL HALIDE		
GLVR175MH	175	Multi-Tap
PULSE START		
GLVR70MH	70	Multi-Tap
GLVR100MH	100	Multi-Tap
GLVR150MH	150	Multi-Tap
GLVR175MHPS	175	Multi-Tap



DIMENSIONS

Width	Height	Depth
15"	15"	11 1/4"

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Coin plugs on sides and back
- Extended vandal resistant polycarbonate lens with stainless steel screws
- Gasket
- Reflector
- Pulse start medium base socket and bracket
- Vertical Lamp mount
- Master carton

ACCESSORIES

Swivel Pendant Mount
Reducer Bushing
Round Electrical Box
Die Cast Back Plate
Liquid Tight Connector
Cordsets
Downrods
Highly Polished Reflector