

TEDDICO

LIGHTING SPECIFICATION SHEET

LARGE VANDAL RESISTANT

APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

DIFFUSER

One piece, injection molded, heat resistant polycarbonate with UV inhibitors to reduce yellowing.

HOUSING

Die cast housing with a Chromate Conversion Coating and textured bronze finish with a polycarbonate lens.



DIMENSIONS

	<i>Width</i>	<i>Height</i>	<i>Depth</i>
VR150	12 3/8"	12 3/8"	8 5/8"
VR120	12"	12"	5 1/2"

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
HIGH PRESSURE SODIUM		
VR100	100	120 Volt
VR150	150	120 Volt
METAL HALIDE		
VR175MH	175	Multi-Tap
PULSE START		
VR100MH	100	Multi-Tap
VR125MH	125	Multi-Tap
VR150MH	150	Multi-Tap
INCANDESCENT		
VR120	2x60	120 Volt
FLOURESCENT		
VRL84EL	2x42	120 Volt
VRL26MG	2x13	120 Volt
VRL52EL	2x26	120 Volt

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- Gasket
- Porcelain medium base socket and bracket white reflector

ACCESSORIES

- Clear Polycarbonate Lens
- White Polycarbonate Lens
- Internal Reflector
- External Hood