

TEDDICO

LIGHTING SPECIFICATION SHEET

MEDIUM VANDAL RESISTANT

APPLICATION:

Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL and CSA_{us} listed for wet and damp locations.

HOUSING

Die cast housing with a Cromate Conversion Coating and textured bronze finish.

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast
HIGH PRESSURE SODIUM		
VR35	35	120 Volt
VR50	50	120 Volt
VR70	70	120 Volt
INCANDESCENT		
VR75	75	120 Volt
ELECTRONIC FLUORESCENT		
VR42	42	120 Volt
MAGNETIC FLUORESCENT		
VR18	2x9	120 Volt
VR26	2x13	120 Volt



DIMENSIONS

	Width	Height	Depth
VR35	9"	9"	7 1/4"
VR42	8 1/2"	8 1/2"	7 1/4"

BALLAST

Class H insulated, NPF 120v 60Hz reactor High pressure sodium. Metal halide Multi-tap.

ADDITIONAL FEATURES

- PC lens
- Gasket
- Medium Socket and bracket
- White Reflector
- Reusable Styrofoam and inner carton
- Master Carton

ACCESSORIES

Clear Lens
White Lens